

LVT COLLECTION

 **REPUBLIC**



BIGGER 5

AN URBAN JUNGLE ADVENTURE



	Characteristics	Standards	Grizzly A / Crocodile
Floor Properties	Total Thickness	EN ISO 24346	2.5mm
	Wear Layer	EN ISO 24340	0.55mm
	Finish		UV COATING
	Surface		Registered Embossing (EIR)
	Installation Method		Gluedown
	Usage Class	EN ISO 10582	21/33
Packing Properties	Planks Size (L*W)		1219*228mm
	Pallet Size (W*L*H)		1000*1250*720mm
	Planks/package (sqm/package)		16 (4.44 sqm)
	Weight/package		21.66kg
	Package/pallet		52
	sqm/pallet		230.8 sqm
	sqm/container		4617 sqm
	Pallet/container		20
Behaviour to Heat	Package/container		1040
	Total weight/pallet		1146kg
Behaviour to Heat	Behaviour to Fire	EN 13501-1	Bfi-S1
	Underfloor Heating Suitability		-30°C to + 70°C
Technical Properties	Static Electrical Propensity	EN 14041	0.5kV, Pass
	Slip Resistance	EN 13893	DS/R9
	Residual Indentation	EN ISO 24343-1	≤ 1%
	Dimensional Stability	EN ISO 23999	≤ 0.15%
Toxic Substances	Formaldehyde / VOC Emission	EN 717-1	E1 / VOC Free
	Greenguard		Pass
	Phthalate Free		Yes



DryBack

• MAXimum strength • MAXimum durability • MAXimum stability • MAXimum style