

GRIZZLY COLLECTION

BIGGER 5
AN URBAN JUNGLE
ADVENTURE



Characteristics	Standards	Grizzly
Total Thickness	EN-ISO 24346	5.5mm
Acoustic Solution Anti Bacterial Bio-Guard	EN-ISO 24346	1.5mm
IIC / STC Rating	ASTM-E492-90 / ASTM- E90-02	55/53
Wear Layer	EN 429 / EN ISO 24340	0.5mm
Box Size		1240*244*60mm
Finish		UV COATING
Surface		EIR+Bevelled Edge
Planks Size (L*W)		1218 (48")*228 (9")mm
Pallet Size (W*L*H)		1000*1250*750mm
Planks/Box (sqm/box)		8 (2.22 sqm)
Box/Pallet		48
Sqm/Pallet		107
Sqm/Container		2346
Gross weight/Pallet		960kg
Behaviour to fire	EN 13501 - 1	Bfi - S1
Slip resistance	EN 13893	R9
Castor chair suitability	EN 425 / ISO4918	Pass
Underfloor heating suitability	EN 1264 - 2	Suitable, max 27°C / 81°F
VOC emissions		No VOC
Installation Method		Glueless Floating
Installation Level		All Grades
Matching Moldings Available		Available
Phthalate Free		Yes
Use in Wet areas	EN 13533	Yes
Residual indentation	ASTM F1914-07	≤ 1%
Dimensional stability	EN - ISO 23999	≤ 0.15%
Resistance to chemicals	ASTM F925-13	Rating 0 - No Change
Impact Resistance	ASTM F1265-03a(2013)	No breakage or crack
Recommended Usage		Residential and Commercial
Temperature Range		(-22°F / -30°C) - (158°F / 70°C)



PureSPCMax®

· MAXimum strength · MAXimum durability · MAXimum stability · MAXimum style